


Low Noise Cable

Features	<ul style="list-style-type: none"> • Minimizes triboelectric/microphonic noise • Triboelectric noise level reduction up to a factor of 1,000 • Assembled with very high quality connectors • Highly shielding coaxial design 																																		
Applications	<ul style="list-style-type: none"> • Low signal current, voltage and charge measurements • Scanning probe microscopy, photodetectors, ionization detectors, piezo- and pyroelectric sensors etc. • For use with FEMTO low noise amplifiers. Strongly recommended for all current amplifiers with gain $\geq 10^7$ V/A • Recommended for low frequency applications (≤ 1 MHz) 																																		
Specifications	<table border="0"> <tr> <td>Test conditions</td> <td>$T_A = 25\text{ }^\circ\text{C}$</td> </tr> <tr> <td>Electrical</td> <td></td> </tr> <tr> <td>Impedance</td> <td>$50\ \Omega \pm 5\ \Omega$</td> </tr> <tr> <td>Capacitance</td> <td>$94\ \text{pF/m} \pm 10\ \text{pF/m}$</td> </tr> <tr> <td>Insulation resistance</td> <td>$> 10^{14}\ \Omega \times \text{m}$</td> </tr> <tr> <td>DC resistance, inner conductor</td> <td>$< 400\ \text{m}\Omega/\text{m}$</td> </tr> <tr> <td>DC resistance, outer conductor</td> <td>$< 40\ \text{m}\Omega/\text{m}$</td> </tr> <tr> <td>Recommended frequency range</td> <td>DC to 1 MHz</td> </tr> <tr> <td>Attenuation</td> <td>$< 0.1\ \text{dB/m}$ (@ DC to 1 MHz)</td> </tr> <tr> <td>General Data</td> <td></td> </tr> <tr> <td>Cable jacket</td> <td>PTFE, $\varnothing 1.92\ \text{mm}$</td> </tr> <tr> <td>Connectors</td> <td>BNC plug (male) to BNC plug (male)</td> </tr> <tr> <td>Minimum bending radius</td> <td>15 mm (fixed installation) 30 mm (free movement)</td> </tr> <tr> <td>Maximum operating voltage</td> <td>AC: $< 46\ \text{V}$ peak-peak, DC: $< 70\ \text{V}$</td> </tr> <tr> <td>Temperature range connectors</td> <td>$-55\text{ }^\circ\text{C}$ to $+155\text{ }^\circ\text{C}$</td> </tr> <tr> <td>Temperature range cable</td> <td>$-190\text{ }^\circ\text{C}$ to $+200\text{ }^\circ\text{C}$</td> </tr> <tr> <td>Weight</td> <td>45 g (for length 1.0 m)</td> </tr> </table>	Test conditions	$T_A = 25\text{ }^\circ\text{C}$	Electrical		Impedance	$50\ \Omega \pm 5\ \Omega$	Capacitance	$94\ \text{pF/m} \pm 10\ \text{pF/m}$	Insulation resistance	$> 10^{14}\ \Omega \times \text{m}$	DC resistance, inner conductor	$< 400\ \text{m}\Omega/\text{m}$	DC resistance, outer conductor	$< 40\ \text{m}\Omega/\text{m}$	Recommended frequency range	DC to 1 MHz	Attenuation	$< 0.1\ \text{dB/m}$ (@ DC to 1 MHz)	General Data		Cable jacket	PTFE, $\varnothing 1.92\ \text{mm}$	Connectors	BNC plug (male) to BNC plug (male)	Minimum bending radius	15 mm (fixed installation) 30 mm (free movement)	Maximum operating voltage	AC: $< 46\ \text{V}$ peak-peak, DC: $< 70\ \text{V}$	Temperature range connectors	$-55\text{ }^\circ\text{C}$ to $+155\text{ }^\circ\text{C}$	Temperature range cable	$-190\text{ }^\circ\text{C}$ to $+200\text{ }^\circ\text{C}$	Weight	45 g (for length 1.0 m)
Test conditions	$T_A = 25\text{ }^\circ\text{C}$																																		
Electrical																																			
Impedance	$50\ \Omega \pm 5\ \Omega$																																		
Capacitance	$94\ \text{pF/m} \pm 10\ \text{pF/m}$																																		
Insulation resistance	$> 10^{14}\ \Omega \times \text{m}$																																		
DC resistance, inner conductor	$< 400\ \text{m}\Omega/\text{m}$																																		
DC resistance, outer conductor	$< 40\ \text{m}\Omega/\text{m}$																																		
Recommended frequency range	DC to 1 MHz																																		
Attenuation	$< 0.1\ \text{dB/m}$ (@ DC to 1 MHz)																																		
General Data																																			
Cable jacket	PTFE, $\varnothing 1.92\ \text{mm}$																																		
Connectors	BNC plug (male) to BNC plug (male)																																		
Minimum bending radius	15 mm (fixed installation) 30 mm (free movement)																																		
Maximum operating voltage	AC: $< 46\ \text{V}$ peak-peak, DC: $< 70\ \text{V}$																																		
Temperature range connectors	$-55\text{ }^\circ\text{C}$ to $+155\text{ }^\circ\text{C}$																																		
Temperature range cable	$-190\text{ }^\circ\text{C}$ to $+200\text{ }^\circ\text{C}$																																		
Weight	45 g (for length 1.0 m)																																		
Dimensions	 <p style="text-align: right;">Length tolerance: +15 mm, -5 mm</p>																																		
Ordering Code	<table border="0"> <thead> <tr> <th>Length</th> <th>Ordering code</th> </tr> </thead> <tbody> <tr> <td>0.1 m</td> <td>CAB-LN1-BB-010</td> </tr> <tr> <td>0.2 m</td> <td>CAB-LN1-BB-020</td> </tr> <tr> <td>0.5 m</td> <td>CAB-LN1-BB-050</td> </tr> <tr> <td>1.0 m</td> <td>CAB-LN1-BB-100</td> </tr> <tr> <td>1.5 m</td> <td>CAB-LN1-BB-150</td> </tr> <tr> <td>2.0 m</td> <td>CAB-LN1-BB-200</td> </tr> <tr> <td>3.0 m</td> <td>CAB-LN1-BB-300</td> </tr> <tr> <td>5.0 m</td> <td>CAB-LN1-BB-500</td> </tr> </tbody> </table>	Length	Ordering code	0.1 m	CAB-LN1-BB-010	0.2 m	CAB-LN1-BB-020	0.5 m	CAB-LN1-BB-050	1.0 m	CAB-LN1-BB-100	1.5 m	CAB-LN1-BB-150	2.0 m	CAB-LN1-BB-200	3.0 m	CAB-LN1-BB-300	5.0 m	CAB-LN1-BB-500																
Length	Ordering code																																		
0.1 m	CAB-LN1-BB-010																																		
0.2 m	CAB-LN1-BB-020																																		
0.5 m	CAB-LN1-BB-050																																		
1.0 m	CAB-LN1-BB-100																																		
1.5 m	CAB-LN1-BB-150																																		
2.0 m	CAB-LN1-BB-200																																		
3.0 m	CAB-LN1-BB-300																																		
5.0 m	CAB-LN1-BB-500																																		

FEMTO Messtechnik GmbH
 Klosterstr. 64
 10179 Berlin · Germany
 Phone: +49 30 280 4711-0
 Fax: +49 30 280 4711-11
 Email: info@femto.de
www.femto.de

Specifications are subject to change without notice. Information provided herein is believed to be accurate and reliable. However, no responsibility is assumed by FEMTO Messtechnik GmbH for its use, nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of FEMTO Messtechnik GmbH. Product names mentioned may also be trademarks used here for identification purposes only.

© by FEMTO Messtechnik GmbH · Printed in Germany